

Advanced Quick Dent Pulling

COMPUSPOT 180AL Aluminium Dent Pulling System

Utilizes capacitive discharge with extra safety features.

Includes welding gun with integrated ground system, 3 welding tips, plus supply of threaded 4, 5 and 6mm pulling studs.

Complete with hand lifter, hook and 3 puller mandrels.

Slide hammer and larger pulling studs optional.

May also be used for dent pulling steel and stainless steel.

Digital touch pad control.

Ready and discharge (trigger) lights in the gun base, let the operator focus on the application rather than the control panel.

115VAC (10A) / 230VAC (6A),
Single phase, 50-60Hz

Capacitance: 66mF

Welding energy: 50J/40V, 1600J/220V

Secondary Open-Circuit Voltage:
 $U_{MIN}:20V, U_{MAX}:25V$



No. Reference

28.CPS180	CompuSpot 180AL
14.CS.00.40	Cart

ALUMATECH Precision Aluminium Reformation Center

The Service Center is a mobile workbench specially designed to provide a productive workplace for the CompuSpot 180AL operator in an aluminium clean room environment.

110V & 220V electrical outlets.
(European, American & Asian models)



Compressed air outlets.
(located on front & back panels)



Front and side perforated panels for tool storage.

Welding gun & Cable supports.

Scratch resistant table top coating.

Sliding drawer & storage shelves.



The service center comes complete with:

The workbench, the CompuSpot 180AL dent puller, Straightening bar, pulling claws, Aluminium hammer & dolly kit, Heat gun, and Infrared Laser Thermometer Sensor.

No. Reference

28.CPS185	AlumaTech Service Center (AMERICA)
28.CPS186	AlumaTech Service Center (EUROPE)

See all the CompuSpot welder accessories available from page 57 to 65

Website: www.amh.ca

Email: sales.amh@amh.ca

CANADA and other countries Tel: (418) 724-4105 Fax: (418) 722-6108

ASIA Tel: +86 10 88 86 40 98

EUROPE Tel: +33 6 16 99 54 08

USA Tel: (330) 519-5874